

P. Ind. Les Salines - C/. Cantabria, 2 08830 Sant Boi de Llobregat (Barcelona) España Tel. + (34) 936 54 86 54 — Fax + (34) 936 54 86 55 e.mail: sales@icp-valves.com — www.icp-valves.com

ICP 2.2 FIG. 150-151 Rev.1 (PS07/F1 Rev.1)

QUALITY CERTIFICATE EN-10204 / 2.2

ICP Valves S.A. CERTIFIES that the manufacture of the valves and/or fittings mentioned below has been fulfilled according to the specifications indicated.

PRODUCT DESCRIPTION

Article Two Pieces Flanged End Ball Valves Fig. 150/151 HIT Size-1/2" to 8" PN 16

TEST DESCRIPTION

Testing Std.: EN 12266-1 YES..... DIN 3230 Teil....... ICP Std PS07/I1...... Other........ Hydraulic Kg/cm2 : Shell ... 24... Seat ... 18... / Pneumatic (barg): Shell...-... Seat 6.... / Functional. Results: Satisfactory, seats tightness as per leakage class A

TYPE MATERIAL

BODY EN-GJL-250 SEAT RING PTFE

ADAPTER EN-GJL-250 BOLT DIN 933 5.6 / 912 8.8

BALL (DN 15 TO 25) AISI 303 ORING FKM
BALL (DN 32 TO 200) AISI 304 NUT DIN 934 8

STEM AISI 304

С	CHEMICAL COMPOSITION:				
С	Mn	S	Р	Si	
3.45	0.60	0.080	0.080	2.10	

PHYSICAL PROPERTIES:			
Tensile St.	Hardness		
Min. 250 N/mm ²	185-220		

NOTES

Visual and control dimensional results satisfactory....X...

ICP Valves S.A. DECLARES that the ICP valves covered by this certificate have been designed and manufactured in accordance with the requirements of the following European Directives:

- Pressure Equipment Directive 2014/68/EU:

Harmonised and non-harmonised technical standards applied:

- PED: EN 10213:2007, EN 12266:2013, 10222:1998, 10204:2004, 1983:2006, 19:2002, EN ISO

17292:2004, for others, please see the ICP catalogue and ICP Instructions Manual.

Electrical and mechanical accessories are not covered by this declaration and must have their own declaration in order for them to be assembled into ICP valves.

See the corresponding Operating Manual.

Alex Velasco Quality Manager Sant Boi de Ll. (Barcelona), julio 30, 2018

CP VALVES, S.A.U.
Cantabria, 2- Pol. Ind. Les Salines
08830 3-41 Boi de Llobregat
Barcelona
Tel. +34 936 548 654
Fax. +34 936 546 655