



Tipo : Type :		E10/L150		do: 10 mm	
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient		Campo di taratura Setting range
E.D. 2014/68/EU - IV Cat.(PED)		150	0,86		100,0 - 150,0 bar
EAC		150	0,86		100,0 - 150,0 bar
ATEX Ex h II 2 Gb		150	0,86		100,0 - 150,0 bar
ATEX Ex h II 2 Db		150	0,86		100,0 - 150,0 bar
ASME VIII Div.1		150	0,629		100,0 - 150,0 bar
Canadian Reg. CRN		150	0,629		100,0 - 150,0 bar
CONFIGURAZIONE - CONFIGURATION					
Materiale Material		Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainles steel		Acciaio inox Stainles steel
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut		Con ghiera With ring nut	
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut		Senza Ghiera Without ring nut	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
Sedi di Tenuta Seal System	PTFE-H -196 / +250 °C PEEK -196 / +200 °C	PTFE-H -196 / +250 °C PEEK -196 / +200 °C Metal -196 / +250 °C		PTFE-H -196 / +250 °C PEEK -196 / +200 °C Metal -196 / +450 °C	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
Connessione Entrata Inlet Connection	G.3/4" - 1" - 1"1/4 ISO228 R.1/2" - 1" - 1"1/4 EN10226 1/2" 3/4"- 1" NPT DN20-25-32 PN16-160 /4" - 1" - 1"1/4 150-1500	G.3/4" - 1" - 1"1/4 ISO228 R.3/4" - 1" - 1"1/4 EN1022 3/4" - 1" - 1"1/4 NPT 1" - 1"1/2 Tri Clamp DN20-25 PN16-160 3/4" - 1" 150-1500 lb		G.3/4" - 1" - 1"1/4 ISO228 R.3/4" - 1" - 1"1/4 EN1022 3/4" - 1" - 1"1/4 NPT 1" - 1"1/2 Tri Clamp DN20-25 PN16-160 3/4" - 1" 150-1500 lb	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
Connessione Uscita Outlet Connection	G.1"1/4 ISO228 DN32 PN16-160 1"1/4 150-1500 lb	G.1"1/4 ISO228 1"1/2 Tri Clamp DN32 PN16-160 1"1/4 150-1500 lb		G.1"1/4 ISO228 1"1/2 Tri Clamp DN32 PN16-160 1"1/4 150-1500 lb	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
	/	/		/	
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register. On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.					

Note: