

VCTEC

PIPE CONNECTORS



Pipe seals




INFORMATION

Votec pipe connectors are made in EPDM rubber and are used as a transition between different types of pipes and dimensions.

Manufactured in accordance with EN 681-1 and has type approval no. 1122.

Manufacturer's declaration

The production of this product has been carried out in accordance with the type-approval of the production control decision and the documents on which the type-approval decision has been based.



Type approval nr: 1122

Votec Pipe seals

Art nr	Dimension mm	Drill hole mm
2357520	110	121

Use: For thin-walled connection.



2357520

Art nr	Dimension mm	Drill hole mm
2357521	160	171
2357522	200	210



2357521



2357522

Telescopic collar

Art nr	Dimension
2359331	400 x 315, smooth riser
2359338	400 x 315, double-walled riser

Use: The collar is used to mount 315 telescopic tube in 400 well.



2359331



2359338

Art nr	Dimension
2435243	200 x 160, smooth riser

Use: The collar is used to mount 160 telescopic tube in 200 well.



2435243

Installation instructions pipe connectors

1. Ensure that the pipe ends are free of miter residues and degrees.
2. Slide the pipe ends into the connector.
3. Density test the installation.

Pipe seals



Products

For connection of incoming conduit to well or pipeline.

Art nr	Dimension mm	Drill hole mm	Length mm	Internal seal grooves
The seal is without tube stop				
2201009	110	121	60	-
2435244	110	138	70	3 st
2435248	110	138	90	5 st
2435245	160	186	70	3 st
2435249	160	186	90	5 st
2435247	200	226	70	3 st
2435250	200	226	90	5 st
2201010	160	171	60	-
2358706	200	210	60	-
The seal is fitted with a tube stop				
2435251	110	127	60	-
2435252	160	177	60	-



2201009



2435244



2435250



2435245



2435248



2201010



2435249



2435247



2358706



2435251



2435252

Hole saws

Art nr	Dimension
2350117	Hole saw \varnothing 127 x 100 mm
2350118	Hole saw \varnothing 138 x 100 mm
2350123	Hole saw \varnothing 172 x 100 mm
2350119	Hole saw \varnothing 177 x 100 mm
2350120	Hole saw \varnothing 186 x 100 mm
2350124	Hole saw \varnothing 212 x 100 mm
2350121	Hole saw \varnothing 226 x 100 mm

Novipro Hole saws with hardened tooth points and a cutting depth of 100 mm. They are specially developed for hole punching on plastic wells and drain pipes where a deeper hole saw is required. The hole saws are hand welded in a high quality piece of steel and are available in dimensions 127–226 mm.



Art nr	Dimension
2350115	Center drill in steel, 150 mm, spare part drill
2350116	Hole saw holder in A2 steel, thread 5/8 ", complete with drill bit

