

THREADED PIPES – SS EN 10255 MEDIUM/HEAVY

Medium Grey threaded without coupling 6 m/length

Item No.	DN
225030	25
225031	32
225032	40
225033	50



Medium Grey threaded without coupling 3 m/length

Item No.	DN
225040	25
225041	32
225042	40
225043	50
1222124	100



Medium Galvanized non-threaded 6 m/length

Item No.	DN
1222330	15
1222348	20
1222355	25
1222363	32
1222371	40
1222389	50
1222397	65
1222405	80

DN	Dimension	Weight kg/m
8	13,5 x 2,3	0,64
10	17,2 x 2,3	0,84
15	21,3 x 2,6	1,22
20	26,9 x 2,6	1,56
25	33,7 x 3,2	2,41
32	42,4 x 3,2	3,10
40	48,3 x 3,2	3,56
50	60,3 x 3,6	5,03
65	76,1 x 3,6	6,42
80	88,9 x 4,0	8,36
100	114,3 x 4,5	12,2

Medium Galvanized Threaded with Coupling 6 m/length

Item No.	DN
1222033	15
1222041	20
1222058	25
1222066	32
1222074	40
1222082	50
1222090	65
1222108	80
1222124	100

DN	Dimension	Weight kg/m
-	-	-
10	17,2 x 2,9	1,02
15	21,3 x 3,2	1,44
20	26,9 x 3,2	1,87
25	33,7 x 4,0	2,93
32	42,4 x 4,0	3,79
40	48,3 x 4,0	4,37
50	60,3 x 4,5	6,19
65	76,1 x 4,5	7,93
-	-	-
-	-	-

GÄNGRÖR – SS EN 10255 MEDIUM/TJOCKA

Medium Grå gängade utan muff – 6 m/längd

Art.nr	DN
225030	25
225031	32
225032	40
225033	50



Medium Grå gängade utan muff – 3 m/längd

Art.nr	DN
225040	25
225041	32
225042	40
225043	50
1222124	100



Medium Galv ogängade – 6 m/längd

Art.nr	DN
1222330	15
1222348	20
1222355	25
1222363	32
1222371	40
1222389	50
1222397	65
1222405	80

DN	Dimension	Vikt kg/m
8	13,5 x 2,3	0,64
10	17,2 x 2,3	0,84
15	21,3 x 2,6	1,22
20	26,9 x 2,6	1,56
25	33,7 x 3,2	2,41
32	42,4 x 3,2	3,10
40	48,3 x 3,2	3,56
50	60,3 x 3,6	5,03
65	76,1 x 3,6	6,42
80	88,9 x 4,0	8,36
100	114,3 x 4,5	12,2

Medium Galv Gängade med muff, 6 meter/längd

Art.nr	DN
1222033	15
1222041	20
1222058	25
1222066	32
1222074	40
1222082	50
1222090	65
1222108	80
1222124	100

DN	Dimension	Vikt kg/m
-	-	-
10	17,2 x 2,9	1,02
15	21,3 x 3,2	1,44
20	26,9 x 3,2	1,87
25	33,7 x 4,0	2,93
32	42,4 x 4,0	3,79
40	48,3 x 4,0	4,37
50	60,3 x 4,5	6,19
65	76,1 x 4,5	7,93
-	-	-
-	-	-