


KIT-36PK4Z5 (S-2545PK4E + U-36PZ3E5)



PACi NX-serien Standard väggmonterad - PK4 - R32		
		3.6 kW
Input power heating (Min)	kW	0,23
Outdoor dimension (Width)	mm	824
Outdoor air flow (Heat)	m³/min	34,0
Outdoor air flow (Cool)	m³/min	33,6
nanoe X Generator		Mark 3
Moisture removal volume	L/h	1,0
Input power heating (Max)	kW	1,30
Outdoor dimension (Depth)	mm	299
COP (Max) (1)	W/W	5,65
COP (Min) (1)	W/W	3,54
Heating capacity (Max)	kW	4,6
Heating capacity (Min)	kW	1,3
Input power cooling (Max)	kW	1,07
Input power cooling (Min)	kW	0,26
EER (Max) (1)	W/W	5,00
EER (Min) (1)	W/W	3,74
Cooling capacity (Max)	kW	4,0
Current in heating (1p 220V / 3p 380)	A	4,10
Indoor sound pressure (Lo) (5)	dB(A)	30
Indoor sound pressure (Med) (5)	dB(A)	36
Indoor sound pressure (Hi) (5)	dB(A)	41
Indoor air flow (Lo)	m³/min	7,0
Indoor air flow (Med)	m³/min	9,5
Indoor air flow (Hi)	m³/min	11,5
Indoor sound power (Lo)	dB(A)	46
Indoor sound power (Med)	dB(A)	52
Current in heating (1p 240V / 3p 415)	A	3,80
Current in heating (1p 230V / 3p 400)	A	3,95
Cooling capacity (Min)	kW	1,3
Current in cooling (1p 240V / 3p 415)	A	3,85
Current in cooling (1p 230V / 3p 400)	A	4,00
Current in cooling (1p 220V / 3p 380)	A	4,15
Remote controller		CZ-RTC5B
Outdoor sound power (Heat -Hi)	dB(A)	66
Outdoor sound power (Cool -Hi)	dB(A)	64
Outdoor sound pressure (Heat -Hi)	dB(A)	47
Outdoor sound pressure (Cool -Hi)	dB(A)	46
Elevation difference (in/out) (8)	m	15 / 15
Indoor net weight	kg	9
Input power heating (Nominal)	kW	0,88
Pdesign at -10°C	kW	2,6
SCOP (2)		4,4 A+
Annual energy consumption heating (3)	kWh/a	827
Annual energy consumption cooling (3)	kWh/a	181
Input power cooling (Nominal)	kW	0,90
Pdesign (cooling)	kW	3,5
SEER (2)		6,8 A++
Outdoor net weight	kg	32
Outdoor dimension (Height)	mm	619

PACi NX-serien Standard väggmonterad - PK4 - R32		
		3.6 kW
Operating range (Cool - Min)	°C	-10
Indoor dimension (Height)	mm	290
Pipe length range	m	3 till 15
Pipe diameter (Liquid)	Inch (mm)	1/4 (6,35)
Operating range (Heat - Max)	°C	+24
Operating range (Heat - Min)	°C	-15
Operating range (Cool - Max)	°C	+43
Outdoor unit		U-36PZ3E5
Indoor unit		S-2545PK4E
Kit		KIT-36PK4Z5
Additional gas amount	g/m	0,87 / 0,59
Pipe length for additional gas	m	7,5
Pipe diameter (Gas)	Inch (mm)	1/2 (12,70)
Indoor dimension (Depth)	mm	214
Indoor dimension (Width)	mm	765
Refrigerant (R32) / CO2 Eq.	kg / T	10
Indoor sound power (Hi)	dB(A)	57
EER (Nominal) (1)	W/W	3,89
COP (Nominal) (1)	W/W	4,09
Outdoor power source	V	220 - 230 - 240
Heating capacity (Nominal)	kW	3,6
Cooling capacity (Nominal)	kW	3,5

Kompletterande produkter

