

Medium grey Threaded without coupling

- Hot stretched reduced tubes according to EN10255M
- Material: S195T
- Threaded end according to EN10226-1
- Protective coating in grey colour
- The paint is melamine-based
- Standard coating thickness: minimum 25 µm (corresponds to C1 and C2) RAL 7012



Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
225030	25	6	33,7 x 3,2	2,41
225031	32	6	42,4 x 3,2	3,10
225032	40	6	48,3 x 3,2	3,56
225033	50	6	60,3 x 3,6	5,03
225040	25	3	33,7 x 3,2	2,41
225041	32	3	42,4 x 3,2	3,10
225042	40	3	48,3 x 3,2	3,56
225043	50	3	60,3 x 3,6	5,03

Medium blue Threaded without coupling

- Hot stretched reduced tubes according to EN10255M
- Material: S195T
- Threaded end according to EN10226-1
- Protective coating in blue colour
- The paint is melamine-based
- Standard coating thickness: minimum 25 µm (corresponds to C1 and C2)



Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
1221192	10	6	17,2 x 2,3	0,84
1221193	15	6	21,3 x 2,6	1,22
1221194	20	6	26,9 x 2,6	1,56
1221195	25	6	33,7 x 3,2	2,41
1221196	32	6	42,4 x 3,2	3,10
1221197	40	6	48,3 x 3,2	3,56
1221198	50	6	60,3 x 3,6	5,03
1221226	10	3	17,2 x 2,3	0,84
1221227	15	3	21,3 x 2,6	1,22
1221228	20	3	26,9 x 2,6	1,56
1221229	25	3	33,7 x 3,2	2,41
1221230	32	3	42,4 x 3,2	3,10
1221231	40	3	48,3 x 3,2	3,56
1221232	50	3	60,3 x 3,6	5,03

Medium galv Threaded with coupling

- Hot stretched reduced tubes according to EN10255M
- Material: S195T
- Threaded end according to EN10226-1
- Galvanized according to EN10240 A1
- External galvanization thickness: minimum 25 µm, minimum 28 µm over the weldseam



Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
1222025	10	6	17,2 x 2,3	0,84
1222033	15	6	21,3 x 2,6	1,22
1222041	20	6	26,9 x 2,6	1,56
1222058	25	6	33,7 x 3,2	2,41
1222066	32	6	42,4 x 3,2	3,10
1222074	40	6	48,3 x 3,2	3,56
1222082	50	6	60,3 x 3,6	5,03
1222090	65	6	76,1 x 3,6	6,42
1222108	80	6	88,9 x 4,0	8,36
1222124	100	6	114,3 x 4,5	12,2

Medium galv Non-threaded

- Hot stretched reduced tubes according to EN10255M
- Material: S195T
- Plain end
- Galvanized according to EN10240 A1
- External galvanization thickness: minimum 25 µm, minimum 28 µm over the weldseam



Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
1222330	15	6	21,3 x 2,6	1,22
1222348	20	6	26,9 x 2,6	1,56
1222355	25	6	33,7 x 3,2	2,41
1222363	32	6	42,4 x 3,2	3,10
1222371	40	6	48,3 x 3,2	3,56
1222389	50	6	60,3 x 3,6	5,03

Heavy black Non-threaded

- Hot stretched reduced tubes according to EN10255H
- Material: S195T
- Plain end
- Red marked



Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
1224336	15	6	21,3 x 3,2	1,22
1224344	20	6	26,9 x 3,2	1,56
1224351	25	6	33,7 x 4,0	2,41
1224369	32	6	42,4 x 4,0	3,10
1224377	40	6	48,3 x 4,0	3,56
1224385	50	6	60,3 x 4,5	5,03
1224393	65	6	76,1 x 4,5	6,42
1224401	80	6	88,9 x 4,5	8,36
1224427	100	6	114,3 x 5,4	12,2

Medium black Non-threaded

- Hot stretched reduced tubes according to EN10255M
- Material: S195T
- Plain end



* Note! Item 225020 is sold in bundles, not individually

Item No.	DN	Length (m)	Dimension (mm)	Weight (kg/m)
225020*	10	6	17,2 x 2,3	0,84
1220326	10	6	17,2 x 2,3	0,84
1220334	15	6	21,3 x 2,6	1,22
1220342	20	6	26,9 x 2,6	1,56
1220359	25	6	33,7 x 3,2	2,41
1220367	32	6	42,4 x 3,2	3,10
1220375	40	6	48,3 x 3,2	3,56
1220383	50	6	60,3 x 3,6	5,03
1220391	65	6	76,1 x 3,6	6,42
1220409	80	6	88,9 x 4,0	8,36
1220425	100	6	114,3 x 4,5	12,2

Medium grå Gängade utan muff

- Varmsträcksreducerade rör enligt EN10255M
- Material: S195T
- Gängad ände enligt EN10226-1
- Skyddsmålade i grå kulör
- Färgen är Melamin-baserad
- Standard färgtjocklek: min 25 µm (motsvarar C1 och C2)
- RAL 7012



Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
225030	25	6	33,7 x 3,2	2,41
225031	32	6	42,4 x 3,2	3,10
225032	40	6	48,3 x 3,2	3,56
225033	50	6	60,3 x 3,6	5,03
225040	25	3	33,7 x 3,2	2,41
225041	32	3	42,4 x 3,2	3,10
225042	40	3	48,3 x 3,2	3,56
225043	50	3	60,3 x 3,6	5,03

Medium blå Gängade utan muff

- Varmsträcksreducerade rör enligt EN10255M
- Material: S195T
- Gängad ände enligt EN10226-1
- Skyddsmålade i blå kulör
- Färgen är Melamin-baserad
- Standard färgtjocklek: min 25 µm (motsvarar C1 och C2)
- RAL 5005



Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
1221192	10	6	17,2 x 2,3	0,84
1221193	15	6	21,3 x 2,6	1,22
1221194	20	6	26,9 x 2,6	1,56
1221195	25	6	33,7 x 3,2	2,41
1221196	32	6	42,4 x 3,2	3,10
1221197	40	6	48,3 x 3,2	3,56
1221198	50	6	60,3 x 3,6	5,03
1221226	10	3	17,2 x 2,3	0,84
1221227	15	3	21,3 x 2,6	1,22
1221228	20	3	26,9 x 2,6	1,56
1221229	25	3	33,7 x 3,2	2,41
1221230	32	3	42,4 x 3,2	3,10
1221231	40	3	48,3 x 3,2	3,56
1221232	50	3	60,3 x 3,6	5,03

Medium galv Gängade med muff

- Varmsträcksreducerade rör enligt EN10255M
- Material: S195T
- Gängad ände enligt EN10226-1
- Galvaniserad enligt EN10240 A1
- Tjocklek på galvaning utvändigt: min 55 µm och min 28 µm över svetslöss



Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
1222025	10	6	17,2 x 2,3	0,84
1222033	15	6	21,3 x 2,6	1,22
1222041	20	6	26,9 x 2,6	1,56
1222058	25	6	33,7 x 3,2	2,41
1222066	32	6	42,4 x 3,2	3,10
1222074	40	6	48,3 x 3,2	3,56
1222082	50	6	60,3 x 3,6	5,03
1222090	65	6	76,1 x 3,6	6,42
1222108	80	6	88,9 x 4,0	8,36
1222124	100	6	114,3 x 4,5	12,2

Medium galv Ogängade

- Varmsträcksreducerade rör enligt EN10255M
- Material: S195T
- Plana ändar
- Galvaniserad enligt EN10240 A1
- Tjocklek på galvaning utvändigt: min 55 µm och min 28 µm över svetslöss



Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
1222330	15	6	21,3 x 2,6	1,22
1222348	20	6	26,9 x 2,6	1,56
1222355	25	6	33,7 x 3,2	2,41
1222363	32	6	42,4 x 3,2	3,10
1222371	40	6	48,3 x 3,2	3,56
1222389	50	6	60,3 x 3,6	5,03

Tjocka svarta Ogängade

- Varmsträcksreducerade rör enligt EN10255H
- Material: S195T
- Plana ändar
- Rödmarkerade



Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
1224336	15	6	21,3 x 3,2	1,22
1224344	20	6	26,9 x 3,2	1,56
1224351	25	6	33,7 x 4,0	2,41
1224369	32	6	42,4 x 4,0	3,10
1224377	40	6	48,3 x 4,0	3,56
1224385	50	6	60,3 x 4,5	5,03
1224393	65	6	76,1 x 4,5	6,42
1224401	80	6	88,9 x 4,5	8,36
1224427	100	6	114,3 x 5,4	12,2

Medium svarta Ogängade

- Varmsträcksreducerade rör enligt EN10255H
- Material: S195T
- Plana ändar



*OBS! Artikel 225020 säljs i hela buntar, ej styck

Art. nr	DN	Längd (m)	Dimension (mm)	Vikt (kg/m)
225020*	10	6	17,2 x 2,3	0,84
1220326	10	6	17,2 x 2,3	0,84
1220334	15	6	21,3 x 2,6	1,22
1220342	20	6	26,9 x 2,6	1,56
1220359	25	6	33,7 x 3,2	2,41
1220367	32	6	42,4 x 3,2	3,10
1220375	40	6	48,3 x 3,2	3,56
1220383	50	6	60,3 x 3,6	5,03
1220391	65	6	76,1 x 3,6	6,42
1220409	80	6	88,9 x 4,0	8,36
1220425	100	6	114,3 x 4,5	12,2